

RESMAX HYDRAULIC OILS – ISO 5, 10, 15, 22, 32, 46 & 68 are a range of premium quality industrial hydraulic oils, manufactured from a blend of solvent refined mineral oils and a multipurpose hydraulic oil additive package.

RES LUBRICANTS

APPLICATION

For use in both closed and total loss systems where a hydraulic operating fluid is required.

RES LUBRICANTS

BENEFITS

- Suitable for a wide range of other industrial applications.
- Extensive range of viscosities to meet most requirements.
- Benefiting from a four fold additive treatment which gives anti-wear, anti-oxidation, anti-corrosion and low foaming properties.
- Thermally stable in extreme conditions of temperature and load which supports resistance to degradation.

RES LUBRICANTS

TYPICAL PROPERTIES

	ISO Viscosity @ 40°C	ISO Viscosity @ 100°C	Density @ 15°C
RESmax Hydraulic Oil – ISO 5	5	2.0	0.812
RESmax Hydraulic Oil – ISO 10	10	3.0	0.841
RESmax Hydraulic Oil – ISO 15	15	4.0	0.855
RESmax Hydraulic Oil – ISO 22	22	4.1	0.866
RESmax Hydraulic Oil – ISO 32	32	4.9	0.875
RESmax Hydraulic Oil – ISO 46	46	6.3	0.875
RESmax Hydraulic Oil – ISO 68	68	8.3	0.880

NB – Higher viscosities available, manufactured to order.

RES LUBRICANTS

PERFORMANCE STANDARDS

- Hagglunds Denison HF-2, HF-0
- Sperry Vickers 1-286-S
- Cincinnati Milacron P-68, P-69, P-70
- DIN 51524 Part 2 (HLP)
- AFNOR NF E 48-603 (HM)
- FZG Damaging Stage 12
- Denison Filterability TP 02100
- US Steel 126 / 127 For R & O Hydraulic Fluids

RES LUBRICANTS

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.