

Last Updated: 19.02.2014

Product Code: IP 0391

RESTEC 30 is a medium viscosity rust preventative dewatering fluid which leaves a thin protective film. RESTec 30 is a blend of corrosion inhibitors and waxes in a hydrocarbon base. Will give 3 – 6 months indoor storage protection and 2 – 4 months covered outdoor protection.

RES LUBRICANTS

APPLICATION

Use as received and apply by spray, brush or dipping in a well ventilated area. Leaves a waxy film on drying.

RES LUBRICANTS

BENEFITS

- Safe on both ferrous and non-ferrous metals.
- Provides short to medium term protection of metal components when stored undercover.
- Easily removed with hydrocarbon solvents.
- Excellent penetration.
- Non staining.
- Ideal as a protectant for agricultural machinery , steel stocks etc.

RES LUBRICANTS

TYPICAL PROPERTIES

Appearance:	Fluid Oil	Specific Gravity @ 15.6 ⁰ C:	0.8342
Colour:	Amber	Indoor Protection:	3 – 6 Months
Flash Point:	64 ⁰ C	Kinematic Viscosity @ 40 ⁰ C:	8.5 cSt

RES LUBRICANTS

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Supplier: Ryona Engineering Supplies LTD Unit 2, Holbrook park estate, Holbrooks, Coventry, CV64AB

Tel: 02476 665454

Fax: 02476 665453

Email: Sales@ryona-supplies.co.uk