

Last Updated: 01 October 2007
Product Codes: IS0105; IS0106; IS0078; IS0339
IS0276; IS0079; IS0460; IS0805

SLIDEWAY is the group name for machine tool lubricants of various viscosities.

RES LUBRICANTS

APPLICATION

Use as received for the lubrication of slideways at the manufacturers recommended viscosity.

RES LUBRICANTS

BENEFITS

- Anti wear and anti corrosion properties
- Excellent slideway lubricity for smooth, stick free operation

RES LUBRICANTS

TYPICAL PROPERTIES

	Kinematic Viscosity @ 40°C – mm ² /s	Kinematic Viscosity @ 100°C – mm ² /s	Flash Point (COC) – °C	Density @ 15°C	Pour Point – °C
Slideway 32	32	5.2	205	0.875	-25
Slideway 46	46	6.5	210	0.878	-33
Slideway 68	68	8.5	225	0.880	-24
Slideway 100	100	11.0	233	0.886	-20
Slideway 150	150	14.5	223	0.890	-15
Slideway 220	220	18.5	230	0.892	-15
Slideway 320	320	24.0	258	0.893	-15
Slideway 460	460	30.0	264	0.894	-12

RES LUBRICANTS

PERFORMANCE STANDARDS

- The CGLP oils fulfill
 - DIN 51524 Part 2 (HLP)
 - DIN 51517 Part 3 (CLP)
- ISO 6743 – 13

RES LUBRICANTS

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.